PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

A23K

(11) International Publication Number: WO 98/54980

(43) International Publication Date: 10 December 1998 (10.12.98)

(21) International Application Number: PCT/EP98/03327

(22) International Filing Date: 4 June 1998 (04.06.98)

(71) Applicant (for all designated States except US):
GIST-BROCADES N.V. [NL/NL]; Wateringseweg 1,
P.O. Box 1, NL-2600 MA Delft (NL).

(72) Inventors; and
(75) Inventors/Applicants (for US only): BARENDSE, Rudolf, Carolus, Maria [NL/NL]; Van Bossestraat 9, NL-2613 CM Delft (NL). MEESTERS, Gabriel, Marinus, Henricus [NL/NL]; Hof van Saffier 9, NL-2614 TJ Delft (NL). HARZ, Hans-Peter [DE/DE]; Am Monschbusch 22,

D-67373 Dubenhofen (DE).

(74) Agent: WRIGHT, Simon, Mark; J.A. Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5LX (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: CARBOHYDRATE-BASED ENZYME GRANULATES

(57) Abstract

A process for the preparation of an enzyme-containing granulate is disclosed where an aqueous enzyme-containing liquid is mixed with an edible carbohydrate-based solid carrier, such as starch, mechanically processed into granules, and subsequently dried. This enzyme granulate is suitable for the manufacture of animal feed compositions by mixing feed ingredients with the granulate, treating with steam and pelleting. The compositions show improved enzyme stability during the pelleting process.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda .
BY	Belarus	IS	Iceland	MW	Malawi .	US	United States of America
CA	Canada .	iT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyżstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon	•	Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	u	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

CARBOHYDRATE-BASED ENZYME GRANULATES

Field of the Invention

The present invention relates to the formulation of enzymes, preferably feed-enzymes, into carbohydrate (e.g. starch-)containing granulates, and to processes for the preparation of such enzyme-containing granulates. These (edible) granulates can then be used in animal feeds.

Background of the Invention

The use of various enzymes in animal, e.g.

livestock, feed has become almost common practice. These enzymes are usually produced by culturing microorganisms in large scale fermenters operated by industrial enzyme producers. At the end of the fermentation the resulting "broth" is usually subjected to a series of filtration steps to separate the biomass (the microorganisms) from the desired enzyme (in solution). The enzyme solution is either then sold as a liquid (often after addition of various stabilizers) or processed to a dry formulation.

Enzyme liquid and dry formulations are used on a commercial scale by the feed industry. Liquid formulations may be added to the feed after pelleting in order to avoid

- 2 -

heat inactivation of the enzyme(s) which would occur during
the pelleting process. However the amounts of enzyme in the
final feed preparations are usually very small which makes it
difficult to achieve a homogenous distribution of the enzyme
in the feed, and liquids are notoriously more difficult to
mix evenly than dry ingredients. In addition one needs
specialised (expensive) equipment to add liquids to the feed
after pelleting which is not currently available at most feed
mills (due to the extra cost).

Dry formulations of enzyme(s), on the other hand, have the disadvantage of heat-inactivation of the enzymes during pelleting. Preferred manufacturing protocols in the feed industry involve steam pelleting where the feed is subjected to steam injection(s) prior to pelleting. In the subsequent pelleting step the feed is forced through a matrix or die and the resulting strips are cut into suitable pellets of variable length. The moisture content immediately before pelleting is generally between 18% and 19%. During this process temperatures may rise to 60-95°C. The combined effect of high moisture content and high temperature is detrimental to most enzymes. These disadvantages are also encountered in other types of thermomechanical treatments such as extrusion and expansion.

In order to try and overcome these problems

25 EP-A-0,257,996 (Cultor Ltd) suggests that the stability of enzymes in feed processing could be increased by the preparation of an enzyme "premix" where an enzyme-containing solution is absorbed onto a grain-based carrier consisting of flour, and the premix is subsequently pelleted and dried.

- 3 -

However, these flour-based premixes are not suitable for gentler methods of processing (of the dough-like premix) into granulates, such as low-pressure extrusion or high shear granulation, because of the gluey character of the flour-based premixes.

Various enzyme manufacturers have developed alternative formulation methods to try to improve the stability of dry enzyme products during pelleting and storage.

formulation consisting of a enzyme-containing "T-granulate" that is coated with a high melting wax or fat alleged to improve resistance to pelleting conditions. The granulate is prepared by mixing a dry inorganic (e.g. sodium sulphate)

15 filler with the enzyme solution in a high shear granulator.

EP-A-0,569,468 teaches that any beneficial effect of the coating with respect to pelleting stability is specific for the type of granulate coated, which in this case is based on a sodium sulphate filler. However, the absorption capacity

20 of these (sodium sulphate) fillers is much less than that of carriers such as flour, which is undesirable if one wishes to produce more concentrated enzyme-containing granulates.

In addition, the granulates have a wide particle size distribution which makes it difficult to obtain a homogeneous enzyme concentration throughout. Moreover the bioavailability of the enzyme to the animal is decreased by the wax or fat coating.

WO-A-97/16076 (Novo Nordisk) also refers to the use of waxes and other water-insoluble substances in particulates

- 4 -

but here they are employed as a matrix material.

There is thus a need for stable formulations of enzymes that are based on a carrier that is suitable for granulation methods other than pelleting and that can have a high absorption capacity.

Description of the Invention

In a first aspect of the present invention there is provided a process for the preparation of an enzyme-containing granulate suitable for use in an animal feed, the process comprising processing an enzyme, a solid carrier comprising at least 15% (w/w) of an edible carbohydrate polymer and water in appropriate relative amounts to obtain enzyme-containing granules, and subsequently drying the granules. The enzyme-containing granulate produceable by this process (which forms the second aspect of the invention, which also covers a granulate comprising dried granules formed from an enzyme and a solid carrier which comprises at least 15% (w/w) of an edible carbohydrate polymer) seeks to solve or at least mitigates the problems encountered in the prior art.

The invention can thus provide processes for the preparation of enzyme formulations in the form of granulates that use the carbohydrate as a carrier. The carrier may be in particulate or powder form. The enzyme and water are preferably provided as an enzyme-containing (preferably aqueous) liquid, such as a solution or a slurry, which can be mixed with the solid carrier and allowed to absorb onto the

carrier. During or after the mixing, the enzyme-containing liquid and the carrier are processed into a granulate, which can then subsequently be dried. The use of the carbohydrate carrier may allow the absorption of large amounts of

5 enzyme-containing liquid (and therefore enzyme). The mixture may be used to form a plastic paste or non-elastic dough that can readily be processed into granules, for example it is extrudable. Suitably the carrier is non-fibrous which allows for easier granulation: fibrous materials can prevent

10 granulation by extrusion.

A number of prior art documents that refer to pellets containing various enzymes, but these find use as detergents, often in washing compositions. In contrast, the present application finds use in animal feeds and for that reason the granulates of the invention are edible (by animals) and preferably also digestible. It will therefore not be surprising that the granulates, granules and compositions of the invention are free of soap, detergents and bleach or bleaching compounds, zeolites, binders, fillers (TiO₂, kaolin, silicates, talc etc) to name but a few.

The edible carbohydrate polymer should be chosen so that it is edible by the animal for whom the feed is intended, and preferably digestible as well. The polymer preferably comprises glucose (e.g. a glucose-containing polymer), or $(C_6H_{10}O_5)_n$, units. Preferably the carbohydrate polymer comprises α -D-glucopyranose units, amylose (a linear $(1\rightarrow4)$ α -D-glucan polymer) and/or amylopectin (a branched D-glucan with α -D- $(1\rightarrow4)$ and α -D- $(1\rightarrow6)$ linkages). Starch is the preferred carbohydrate polymer. Other suitable

glucose-containing polymers that can be used instead of, or in addition to starch, include α -glucans, β -glucans, pectin (such as proto-pectin), and glycogen. Derivatives of these carbohydrate polymers, such as ethers and/or esters thereof, are also contemplated although gelatinised starch is best avoided and thus may not be present. Suitably the carbohydrate polymer is water-insoluble.

In the examples described herein corn-, potato- and rice-starch is used. However, starch obtained from other

10 (e.g. plant, such as vegetable or crop) sources such as tapioca, cassava, wheat, maize, sago, rye, oat, barley, yam, sorghum, or arrowroot is equally applicable. Similarly both native or modified (e.g. dextrin) types of starch can be used in the invention. Preferably the carbohydrate (e.g. starch)

15 contains little or no protein, e.g. less than 5% (w/w), such as less than 2% (w/w) preferably less than 1% (w/w).

Regardless of the type of starch (or other carboydrate polymer) it should be in a form that allows it to be used in an animal feed, in other words an edible or digestible form.

At least 15% (w/w) of the solid carrier may comprise the carbohydrate polymer (such as starch). Preferably, however, at least 30% (w/w) of the solid carrier comprises the carbohydrate, optimally at least 40% (w/w). Advantageously the major component of the solid carrier is the carbohydrate (e.g. starch), for example more than 50% (w/w), preferably at least 60% (w/w), suitably at least 70% (w/w), and optimally at least 80% (w/w). These weight percentages are based on the total weight of the non-enzymatic components in the final dry granulate.

- 7 -

In the process of the invention the enzyme and water may be present in the same composition before contacting the solid carrier. In this respect, one may provide an enzyme-containing aqueous liquid. This liquid may be a solution or a slurry that is from, or derived from, a fermentation process. This fermentation process will usually be one in which the enzyme is produced. The fermentation process may result in a broth which contains the microorganisms (which produce the desired enzyme) and an aqueous solution. This aqueous solution, once separated from the microorganisms (for example, by filtration) can be the enzyme-containing aqueous liquid used in the invention. Thus in preferred embodiments the enzyme-containing aqueous liquid is a filtrate.

The amount of enzyme-containing liquid (and so 15 enzyme) that can be absorbed onto the carrier is usually limited by the amount of water that can be absorbed. For natural, granular, starch this can vary between 25 - 30% (w/w), without using elevated temperatures (that cause the starch to swell). In practice the percentage of enzyme liquid to be added to the carbohydrate will often be much larger than this because the enzyme containing liquid will usually contain a significant amount of solids. The enzyme solution can contain about 25% (w/w) solids, as a result of 25 which the carbohydrate (e.g. starch) and enzyme solution can be mixed at a ratio of carbohydrate: enzyme solution of 0.5:1 to 2:1, e.g. 1.2:1 to 1.6:1, such as at a ratio of about 60% (w/w):40% (w/w), respectively. Preferably the amount of liquid added to the solid carrier is such that

- 8

(substantially) all the water in the (aqueous) liquid is absorbed by the carbohydrate present in the solid carrier.

At elevated temperatures starch and other carbohydrate polymers can absorb much larger amounts of water 5 under swelling. For this reason the carbohydrate polymer is desirably able to absorb water (or enzyme-containing aqueous liquids). For example, corn starch can absorb up to three times its weight of water at 60°C and up to ten times at The use of higher temperatures in order to absorb a 10 greater amount enzyme-containing liquid is thus contemplated by the present invention, and indeed is preferable especially when dealing with thermostable enzymes. For these enzymes therefore the mixing of the solid carrier and liquid (or enzyme and water) can be conducted at elevated temperatures 15 (e.g. above ambient temperature), such as above 30°C, preferably above 40°C and optimally above 50°C. Alternatively or in addition the liquid may be provided at this temperature.

However, in general, non-swelling conditions at
lower (e.g. ambient) temperatures are preferred. This may
minimise activity loss arising from instability of (heat
sensitive) enzymes at higher temperatures. Suitably the
temperature during the mixing of the enzyme and water is from
log to 25°C.

The mechanical processing used in the present invention for making the mixture of the enzyme, water (e.g. an enzyme-containing liquid) and the solid carrier into granules (in other words granulating) can employ known techniques frequently used in food, feed and enzyme

- 9 -

formulation processes. This may comprise expansion,
extrusion, spheronisation, pelleting, high shear granulation,
drum granulation, fluid bed agglomeration or a combination
thereof. These processes are usually characterised by an

5 input of mechanical energy, such as the drive of a screw, the
rotation of a mixing mechanism, the pressure of a rolling
mechanism of a pelleting apparatus, the movement of particles
by a rotating bottom plate of a fluid bed agglomerator or the
movement of the particles by a gas stream, or a combination

10 thereof. These processes allow the solid carrier (e.g. in
the form of a powder), to be mixed with the enzyme and water,
for example an enzyme-containing liquid (an aqueous solution
or slurry), and so subsequently granulated.

Alternatively the solid carrier can be mixed with

15 the enzyme (e.g. in a powder form) to which water, such as a
liquid (or slurry) is then added (which can act as
granulating liquid).

In yet a further embodiment of the invention the granulate (e.g. an agglomerate) is formed by spraying or coating the enzyme-containing liquid onto the carrier, such as in a fluid bed agglomerator. Here the resulting granules can include an agglomerate as can be produced in a fluid bed agglomerator.

Preferably the mixing of the enzyme-containing

liquid and the solid carrier additionally comprises kneading of the mixture. This may improve the plasticity of the mixture in order to facilitate granulation (e.g. extrusion).

If the granulate is formed by extrusion this is preferably performed at low pressure. This may offer the

advantage that the temperature of the mixture being extruded will not, or only slightly, increase. Low-pressure extrusion includes extrusion for example in a Fuji Paudal basket- or dome- extruder. Preferably extrusion does not result in the temperature of the material being extruded to rise above 40°C. The extrusion may naturally produce granules (the granules may break off after passage through a die) or a cutter may be employed.

Suitably the granules will have a water content of from 30 to 40%, such as from 33 to 37%. The enzyme content is preferably from 3 to 15, such as 5 to 12% (e.g. at least 50,000ppm).

The granules obtained can be subjected to rounding off (e.g. spheronisation), such as in a spheromiser, e.g. a

15 MARUMERISER™ machine and/or compaction. The granules can be spheronised prior to drying since this may reduce dust formation in the final granulate and/or may facilitate any coating of the granulate.

The granules can then be dried, such as in a fluid bed drier or, in case of the fluid bed agglomeration, can be immediately dried (in the agglomerator) to obtain (solid dry) granulates. Other known methods for drying granules in the food, feed or enzyme industry can be used by the skilled person. Suitably the granulate is flowable.

25 The drying preferably takes place at a temperature of from 25 to 60°C, such as 30 to 50°C. Here the drying may last from 10 minutes to several hours, such as from 15 to 30 minutes. The length of time required will of course depend on the amount of granules to be dried, but as a guide this is

from 1 to 2 seconds per kg of granules.

After drying the granules, the resulting granulate preferably has a water content of from 3 to 10%, such as from 5 to 9%.

A coating may be applied to the granulate to give additional (e.g. favoured) characteristics or properties, like low dust content, colour, protection of the enzyme from the surrounding environment, different enzyme activities in one granulate or a combination thereof. The granules can be coated with a fat, wax, polymer, salt, unguent and/or ointment or a coating (e.g. liquid) containing a (second) enzyme or a combination thereof. It will be apparent that if desired several layers of (different) coatings can be applied. To apply the coating(s) onto the granulates a number of known methods are available which include the use of a fluidised bed, a high shear granulator, a mixer granulator, or a Nauta-mixer.

In other embodiments additional ingredients can be incorporated into the granulate e.g. as processing aids, for further improvement of the pelleting stability and/or the storage stability of the granulate. A number of such preferred additives are discussed below.

Salts may be included in the granulate, (e.g. with the solid carrier or water). Preferably (as suggested in EP-A-0,758,018) inorganic salt(s) can be added, which may improve the processing and storage stability of the dry enzyme preparation. Preferred inorganic salts are water soluble. They may comprise a divalent cation, such as zinc (in particular), magnesium, and calcium. Sulphate is the

most favoured anion although other anions resulting in water solubility can be used. The salts may be added (e.g. to the mixture) in solid form. However, the salt(s) can be dissolved in the water or enzyme-containing liquid prior to mixing with the solid carrier. Suitably the salt is provided at an amount that is at least 15% (w/w based on the enzyme), such as at least 30%. However, it can be as high as at least 60% or even 70% (again, w/w based on the enzyme). These amounts can apply either to the granules or to the granulate.

The granulate may therefore comprise less than 12% (w/w) of the salt, for example from 2.5 to 7.5%, e.g. from 4 to 6%.

If the salt is provided in the water then it can be in an amount of from 5 to 30% (w/w), such as 15 to 25%.

Further improvement of the pelleting stability may

15 be obtained by the incorporation of hydrophobic, gel-forming
or slow dissolving (e.g. in water) compounds. These may be
provided at from 1 to 10%, such as 2 to 8%, and preferably
from 4 to 6% by weight (based on the weight of water and
solid carrier ingredients). Suitable substances include

20 derivatised celluloses, such as HPMC (hydroxy-propyl-methylcellulose), CMC (carboxy-methyl-cellulose), HEC
(hydroxy-ethyl-cellulose); polyvinyl alcohols (PVA); and/or
edible oils. Edible oils, such as soy oil or canola oil, can
be added (e.g. to the mixture to be granulated) as a

25 processing aid, although often it will be preferred that the
granulate does not contain any hydrophobic substances (e.g.
palm oil).

Preferably the granules have a relatively narrow

- 13 -

size distribution (e.g. they are monodisperse). This can facilitate a homogeneous distribution of the enzyme in the granules and/or the enzyme granulate in the animal feed. The process of the invention tends to produce granulates with a narrow size distribution. However, if necessary, an additional step can be included in the process to further narrow the size distribution of the granules, such as screening. The size distribution of the granulate is suitably between 100 μ m and 2000 μ m, preferably between 100 μ m and optimally between 300 μ m and 1600 μ m. The granules may be of irregular (but preferably regular) shape, for example approximately spherical.

The water or enzyme-containing liquid may comprise one or more enzyme(s) and are usually of microbial origin,

5 e.g. obtained from a microbial fermentation. Usually the enzyme will be in an active form (for example it may have catalytic or physiological activity). Preferably the liquid is in a concentrated form, such as an ultra-filtrate (UF), which may allow the production of a granulate with a desired activity level.

Suitable enzyme(s) are those to be included in animal feed which includes pet food. The function of these enzymes is often to improve the feed conversion rate, e.g. by reducing the viscosity or by reducing the anti-nutritional effect of certain feed compounds. Feed enzymes (such as phytase) can also be used, such as to reduce the amount of compounds which are harmful to the environment in the manure. Preferred enzymes for these purposes are: phosphatases, such as phytases (both 3-phytases and 6-phytases) and/or acid

phosphatases; carbohydrases, such as amylolytic enzymes and plant cell wall degrading enzymes of which include cellulases such as β -glucanases, hemicelluloses such as xylanases, or galactanases; peptidases, galactosidases, pectinases,

esterases; proteases, preferably with a neutral and/or acidic pH optimum; and lipases, preferably phospholipases such as the mammalian pancreatic phospholipases A2.

Preferably, the enzyme does not include starch degrading enzymes (for example amylases). In some embodiments proteases may be excluded as these may cause harm if ingested.

If the enzyme is a phosphatase, such as a phytase, then preferably the final granulate will have an activity of from 5,000 to 10,000 such as from 6,000 to 8,000, FTU/g. If the enzyme is a plant cell wall degrading enzyme, for example a cellulase, and in particular a hemicellulose such as xylanase, then the final granulate may have an activity of the enzyme ranging from 3,000 to 100,000, preferably 5,000 to 80,000, and optimally 8,000 to 70,000, EXU/g. If the enzyme is a cellulase, such as β-gluconase, then the final granulate can have an enzyme activity of from 500 to 15,000, preferably from 1,000 to 10,000, and optimally from 1,500 to 7,000, BGU/g.

The granules may comprise from 5 to 20, e.g. from 7 to 15% of the enzyme(s). The enzyme(s) may be naturally occurring or recombinant.

In addition to these enzymes the invention is equally applicable to polypeptides with other biological activities, such as antigenic determinants, for example that

- 15 -

find use in vaccines and/or polypeptides engineered to have an increased content of essential amino acids, of which the biological activity may be sensitive to thermal inactivation, and the term "enzyme" as used herein is to be construed accordingly.

A preferred process according to the invention therefore comprises:

10

15

- a. mixing the water, enzyme and solid carrier comprising at least 15% (w/w) or an edible carbohydrate polymer, for example mixing the solid carrier with an aqueous enzyme-containing liquid;
- b. optionally kneading the resulting mixture;
- c. granulating, for example by mechanical processing, the mixture in order to obtain enzyme-containing granules, for example by using a granulator or by extrusion;
- d. optionally spheronising the granules;
- e. drying the resultant granules to obtain an enzyme-containing granulate.

During the entire process one will aim to keep the maximum temperature to which the enzyme(s) are exposed to below 80°C.

The granulates of the invention are suitable for use in the preparation of an animal feed. In such processes the granulates are mixed with feed substances, either as such, or as part of a premix. The characteristics of the granulates according to the invention allows their use as a component of a mixture which is well suited as an animal feed, especially if the mixture is steam treated and subsequently pelleted.

- 16 -

The dried granules may be visible or distinguishable in such pellets.

Thus a third aspect of the present invention relates to a process for the preparation of animal feed, or a premix 5 or precursor to an animal feed, the process comprising mixing a granulate of the second aspect with one or more animal feed. substances (e.g. seeds) or ingredients. This can then be sterilised, e.g. subjected to heat treatment. The resulting composition is then suitably processed into pellets.

A fourth aspect of the invention relates to a composition comprising a granulate of the second aspect, which composition is preferably an edible feed composition such as an animal feed. This composition is preferably in the form of pellets (there may be 1-5, e.g. 2-4 dried 15 granules per pellet).

10

The composition can have a water content of from 10 to 20%, e.g. from 12-15%. The amount of enzyme(s) is suitably from 0.0005 to 0.0012%, such as at least 5ppm.

A fifth aspect relates to a process for promoting the growth of an animal, the process comprising feeding an animal with a diet that comprises a granulate of the second aspect or a composition of the fourth aspect. Here, the animal diet can include either the granulate itself, or the granulate present in a feed.

Suitably the composition comprises from 0.05 to 2.0, 25 such as 0.3 to 1.0, optimally 0.4 to 0.6 FTU/g of a phosphatase, e.g. a phytase. A xylanase may be present at from 0.5 to 50, e.g. 1 to 40 EXU/g. Alternatively or in addition a cellulase may be present at from 09.1 to 1.0, e.g.

0.2 to 0.4 BGU/g.

A sixth aspect of the present invention relates to the use of the granulate of the second aspect in, or as a component of, an animal feed or for use in an animal diet.

A seventh aspect of the present invention relates to the use of a composition comprising at least 15% (w/w) of an edible carbohydrate polymer as a carrier for an enzyme to improve the pelleting stability of the enzyme.

Suitable animals include farm animals (pigs,

10 poultry, livestock), non-ruminants or monogastric animals

(pigs, fowl, poultry, marine animals such as fish), ruminants

(bovine or ovine, e.g. cows, sheep, goats, deer, calves,

lambs). Poultry includes chickens, hens and turkeys.

Preferred features and characteristics of one aspect

of the invention are equally applicable to another mutatis

mutandis.

The following Examples are presented merely to illustrate the invention, and are not intended, or to be construed as, being limiting.

EXAMPLES

General Materials and Methods

Extrusion tests were performed using a Fuji Paudal DG-L1 basket extruder, with screen openings of 1.0 mm, screen thickness 1.2 mm, operating speed of 70 rpm, and a current of 0.6 - 2.0 A.

The spheroniser was a Fuji Paudal Marumerizer
QJ-400, with a charge volume of 3 litres, plate pitch of
3 mm, retention time of 45-200 seconds and rotating speed of
10 750 rpm.

The high shear granulation tests were conducted using a Lödige type high shear granulator FM20, with a chopper speed of 1500 rpm and a ploughshare speed of 100 rpm. Powder was placed in the granulator and the enzyme-containing liquid was sprayed on top. The resulting granulates were dried in fluid bed drier.

The enzyme solutions used were:

- an ultra-filtrate of an Aspergillus derived phytase with an activity of 16840 FTU/g, and a dry solids content of 22.4% (w/w) (Examples 1 to 7).
 - an ultra-filtrate containing a Trichoderma derived mixture of endo-xylanase and β -glucanase activities of 12680 EXU/g and BGU/g, and a dry solids content of 20.6% (w/w) (Example 8).
- Phytase activity was determined according to the procedure "ISL-method 61696" (manual vanadate assay). $\beta\text{-glucanase activity was determined according to the}$

procedure "ISL-method 62170" (manual viscosimetric assay).

Endo-xylanase activity was determined according to the

procedure "ISL-method 62169" (manual viscosimetric assay).

ISL-methods are obtainable on request from Gist-brocades,

Food Specialties, Agri Ingredients Group, Wateringseweg 1,

P.O. Box 1, 2600 MA, Delft, The Netherlands.

EXAMPLE 1

Preparation of corn starch-based enzyme granulate by kneading, extrusion, spheronisation and drying

An enzyme preparation was obtained by mixing and kneading a mixture of 60% (w/w) of corn starch with 40% (w/w) of an ultra-filtrate containing phytase. This mixture was extruded using the Fuji Paudal basket extruder to obtain a wet extrudate which was then spheronised in the MARUMERISER™ for one minute to obtain round particles of an average diameter of 780 μm. These particles were subsequently dried in a fluid bed drier for 20 minutes at a bed temperature of 40°C, and an inlet temperature of 75°C. Approximately 500kg of the granules were dried in 18 minutes. The thus obtained dry enzyme granulate had an activity of 6980 FTU/g.

EXAMPLE 2

Preparation of a corn starch-based enzyme granulate by high shear granulation and drying

The phytase ultra-filtrate and corn starch were

mixed in a batch type high shear granulator of the Lödige

type, with a batch size of 20 litres. The granulator was

filled with 60% (w/w) of corn starch and 40% (w/w)

ultra-filtrate was sprayed into the mixer during the mixing process. After addition of the ultra-filtrate (10 minutes) the granulator continued mixing for another 5 minutes to allow the particles to be formed and compacted. The thus obtained granules were dried in a fluid bed drier as in Example 1. The resulting granulate had an activity of 7420 FTU/g. The median diameter of the particles was 480 μ m.

EXAMPLE 3

Preparation of a corn starch-based enzyme granulate

10 by mixing, pelleting and drying

A mixture of 40% (w/w) of the phytase ultra-filtrate and 60% (w/w) of corn starch was prepared. The mixture was pelleted using a Schlütter Press type PP85, where the extrudates were cut off by rotating knives at the extruder head, with a die plate containing holes of 1 mm in diameter. The pellets were dried as in Example 1, resulting in a final product with an activity of 7460 FTU/g. The median diameter of the particles was 1080 μ m.

EXAMPLE 4

Preparation of a potato starch-based enzyme granulate containing soy oil and MgSO, additions

by mixing, kneading, pelleting and drying

In a mixer/kneader 30 kg of potato starch was added and 2.5 kg of Soy oil was mixed in. Subsequently the phytase ultra-filtrate was added containing MgSO₄.7H₂O (3.5 kg of MgSO₄.7H₂O was dissolved in 14 kg of ultra-filtrate). The product was mixed thoroughly in the kneader, then extruded

and dried in a fluid bed drier as in Example 1. This resulted in a product of 5870 FTU/g.

EXAMPLE 5

Preparation of a rice starch-based enzyme granulate

5 by mixing, kneading, extrusion, spheronisation and drying

A mixture was prepared by mixing and kneading 62% (w/w) rice starch and 38% (w/w) of the phytase ultra-filtrate. This mixture was extruded using the Fuji Paudal basket extruder to obtain a wet extrudate which was then spheronised in the MARUMERISER™ for one minute to obtain round particles of an average diameter of 785 μm. These particles were subsequently dried in a fluid bed drier as in Example 1. The final activity of the granulate was 7280 FTU/g.

15 EXAMPLE 6

Preparation of a corn starch-based enzyme granulate containing an HPMC addition by mixing, kneading, extrusion, spheronisation and drying

An enzyme preparation was obtained by kneading a

20 mixture of 54% (w/w) of corn starch, 5% of HPMC
(hydroxy-propyl-methyl-cellulose) and 41% (w/w) of a phytase
ultra-filtrate. This mixture was extruded using the Fuji
Paudal basket extruder to obtain a wet extrudate which was
spheronised in the MARUMERISER™ for one minute to obtain

25 round particles of an average diameter of 780 μm. These were
subsequently dried in a fluid bed drier for 20 minutes at
40°C bed temperature, and 75°C inlet temperature. The thus

obtained dry enzyme granulate had an activity of 8470 FTU/g.

EXAMPLE 7

Preparation of a corn starch-based enzyme granulate containing an HEC addition by mixing, kneading, extrusion,

5 spheronisation and drying

An enzyme preparation was obtained by mixing and kneading 54% (w/w) of corn starch, 5% (w/w) of HEC (hydroxy-ethyl-cellulose) with 41% (w/w) of the phytase ultra-filtrate. This mixture was extruded using the Fuji 10 Paudal basket extruder to obtain a wet extrudate which was spheronised in the MARUMERISER™ for one minute to obtain round particles of an average diameter of 780 µm. These were subsequently dried in a fluid bed drier for 20 minutes at 40°C bed temperature, and 75°C inlet temperature. The thus obtained dry enzyme granulate had an activity of 8410 FTU/g.

EXAMPLE 8

Preparation of a corn starch-based enzyme granulate by high shear granulation and drying

In a batch type high shear granulator of the Lödige type, with a batch size of 20 litres, 60% (w/w) of corn starch was mixed with 40% (w/w) of the ultra-filtrate containing endo-xylanase and β -glucanase in the following manner. The granulator was filled with corn starch and the ultra-filtrate was sprayed into the mixer during the mixing process. After addition of the ultra-filtrate (10 minutes) the granulator was operated for another 5 minutes to allow the particles to be formed and compacted. The thus obtained

granules were dried in a fluid bed drier as in Example 1. The resulting granulate had an activity of 13100 EXU/g and 5360 BGU/g.

EXAMPLE 9

5 Comparison of the pelleting stabilities

The different enzyme granulates of the invention were subjected to a pelleting trial and their pelleting stability was compared with those of the standard feed enzyme formulations. The pelleting trial consisted of mixing the enzyme (granulate) with a feed premix at 1000 ppm. This mixture was treated by injection of steam to give a temperature rise to 70°C, after which the mixture was pelleted in a pelleting machine to obtain the feed pellets, which were subsequently dried. This type of process is typical for the feed industry to obtain feed pellets.

For NATUPHOS™, a phytase containing formulation used as a standard, for comparison, was a mixture of wheat middlings with spray dried ultra-filtrate.

For NATUGRAIN^M, an enzyme preparation containing β -glucanase and endo-xylanase, this is a fluid bed prepared granule, made by coating a salt core with an enzyme layer, applied by spraying the core with an ultra-filtrate.

Table 1 summarizes the results of the pelleting trials. It is apparent from Table 1 that the granulates made using a carbohydrate carrier gave improved pelleting yields when compared with standard formulations.

Table 1: Results of the pelleting tests

Example Number	Enzyme activity	of the granules	Enzyme yield after pelleting at 70°C
	FTU/g	EXU/g BGU/g	8
Ex. 1	6980	<u>.</u>	54.9
Ex. 2	7420	_	51.8
Ex. 3	7460	, <u>-</u>	62.8
Ex. 4	5870	-	62.7
Ex. 5	7280		54.7
Ex. 6	8470	-	69.6
Ex. 7	8410		67.3
Ex. 8		13100 5360	61.3 25.8
Standard NATUPHOS™	5250	-	29.8
Standard NATUGRAIN™	_	8150 6030	38.6 10.4

It is clear from Table 1 that the type of granulation method, i.e. mechanical processing, is not critical to addressing the problems to be solved by the invention. Formulations using the carbohydrate polymer 20 provided a much better pelleting stability as compared to the known NATUPHOS™ and NATUGRAIN™ formulations.

CLAIMS

- A process for the preparation of an enzyme-containing granulate suitable for use in an animal feed, the process comprising processing an enzyme, a solid carrier comprising at least 15% (w/w) of an edible carbohydrate polymer and water in appropriate relative amounts to obtain enzyme-containing granules, and subsequently drying the granules.
- 2. A process according to claim 1 wherein the water and enzyme are provided as an enzyme-containing aqueous liquid.
- 3. A process according to claim 2 wherein the liquid is a filtrate derived from a fermentation process resulting in production of the enzyme.
 - 4. A process according to any preceding claim wherein the process comprises:
 - a) mixing an aqueous liquid containing the enzyme with the solid carrier;
- 20 b) mechanically processing the mixture obtained in
 - a) to obtain enzyme-containing granules; and
 - c) drying the enzyme-containing granules obtained in b).
- 5. A process according to any preceding claim
 25 wherein the processing is mechanical and comprises extrusion,
 pelleting, high-shear granulation, expansion, fluid bed
 agglomeration or a combination thereof.
 - 6. A process according to any preceding claim

wherein an enzyme-containing aqueous liquid and the solid carrier are mixed and the resulting mixture kneaded before granulation.

- 7. A process according to any preceding claim

 5 wherein the processing is extrusion performed at low pressure
 and/or in a basket- or dome- extruder.
 - 8. A process according to any preceding claim wherein the granules obtained are spheronised prior to drying.
- 9. An enzyme-containing granulate produceable by a process as defined in any preceding claim.
 - 10. A granulate comprising dried granules formed from an enzyme and a solid carrier which comprises at least (w/w) of an edible carbohydrate polymer.
- 11. A granulate according to claims 9 or 10 wherein the granules comprise at least one divalent cation.
 - 12. A granulate according to any of claims 9 to 11 wherein the granules comprise one or more hydrophobic, gel-forming or water insoluble compound(s).
- 13. A granulate according to claim 12 wherein the hydrophobic, gel-forming or water insoluble compound comprises a derivatised cellulose, polyvinyl alcohol (PVA) or an edible oil.
- 14. A granulate according to claim 13 wherein the
 25 derivatised cellulose is hydroxy-propyl-methyl-cellulose,
 carboxy-methyl-cellulose or hydroxy-ethyl-cellulose and/or
 the edible oil is soy oil or canola oil.
 - 15. A granulate according to any one of claims 9 to 14 wherein the enzyme comprises a phytase, endo-xylanase

and/or a β -glucanase.

- 16. A process for the preparation of an animal feed, or a premix or precursor to an animal feed, the process comprising mixing a granulate as defined in any of claims 9 to 15 with one or more animal feed substance(s) or ingredient(s).
 - 17. A process according to claim 16 wherein the mixture of feed substance(s) and granulate is sterilised or treated with steam, pelletised and optionally dried.
- 18. A composition comprising a granulate as defined in any of claims 9 to 15.
 - 19. A composition according to claim 18 which is an edible feed composition.
- 20. A composition according to claim 18 or 19 which 15 is an animal feed.
 - 21. A composition according to any of claims 18 to 20 which comprises pellets of one or more feed substance(s) or ingredient(s) mixed with a granulate according to any of claims 9 to 15.
- 22. A composition according to claim 21 wherein the ratio of granulate: feed substance(s) or ingredients is at least 1g:1kilo (such as at least 100ppm).
- 23. A composition according to any of claims 18 to 22 which is an animal feed, or a premix or precursor to an animal feed, preparable by a process according to claim 16 or 17.
 - 24. A process for promoting the growth of an animal, the process comprising feeding an animal with a diet that comprises either a granulate as defined in any of claims

- 28 -

9 to 15 or a composition as defined in any of claims 18 to 23.

- 25. Use of a granulate as defined in any of claims 9 to 15 in, or as a component of, an animal feed or for use 5 in an animal diet.
 - 26. Use of a composition comprising at least 15% (w/w) of an edible carbohydrate polymer as a carrier for an enzyme to improve the pelleting stability of the enzyme.
- 27. A process for the preparation of an enzyme-containing granulate, wherein an enzyme-containing liquid and a solid carrier comprising at least 15% (w/w) starch are mechanically processed to obtain enzyme-containing granules which are subsequently dried.

PCT

(22) International Filing Date:

(30) Priority Data:

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

INTERNATIONAL ATTEICATION	I ODDIO		O.	ADDIC TILD ITTI DIVI COCI ZICITIOI	(-0-)	
(51) International Patent Classification 6:				11) International Publication Number:	WO 98/54980	
A23K 1/00, C11D 3/386 // C12N 9/	98	A3	6	43) International Publication Date: 10 D	December 1998 (10.12.98)	
(21) International Application Number:	PCT/EP	98/033	27	(81) Designated States: AL, AM, AT, AU		

4 June 1998 (04.06.98)

97201641.4 4 June 1997 (04.06.97) EP
(34) Countries for which the regional or
international application was filed: AT et al.
60/048,611 4 June 1997 (04.06.97) US

(71) Applicant (for all designated States except US):
GIST-BROCADES N.V. [NL/NL]; Wateringseweg 1,
P.O. Box 1, NL-2600 MA Delft (NL).

(72) Inventors; and
(75) Inventors/Applicants (for US only): BARENDSE, Rudolf, Carolus, Maria [NL/NL]; Van Bossestraat 9, NL-2613 CM Delft (NL). MEESTERS, Gabriel, Marinus, Henricus [NL/NL]; Hof van Saffier 9, NL-2614 TJ Delft (NL). HARZ, Hans-Peter [DE/DE]; Am Monschbusch 22, D-67373 Dubenhofen (DE).

(74) Agent: WRIGHT, Simon, Mark; J.A. Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5LX (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(88) Date of publication of the international search report:
4 March 1999 (04.03.99)

(54) Title: CARBOHYDRATE-BASED ENZYME GRANULATES

(57) Abstract

A process for the preparation of an enzyme-containing granulate is disclosed where an aqueous enzyme-containing liquid is mixed with an edible carbohydrate-based solid carrier, such as starch, mechanically processed into granules, and subsequently dried. This enzyme granulate is suitable for the manufacture of animal feed compositions by mixing feed ingredients with the granulate, treating with steam and pelleting. The compositions show improved enzyme stability during the pelleting process.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ .	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	18	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Келуа	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwc
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Сатегоол	_	Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

PCT/EP 98/03327

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 A23K1/00 C11D //C12N9/98 C11D3/386 IPC 6 According to International Patent Classification (IPC) or to both national classification and IPC 8. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) C11D C12N A23K Documentation searched other than minimum documentation to the extent that such documents are included. In the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Relevant to claim No. Category : Citation of document, with indication, where appropriate, of the relevant passages 1-10.EP 0 257 996 A (SUOMEN SOKERI OY) 12-27 2 March 1988 cited in the application see abstract see page 2, line 1 - line 6 see page 2, 1ine 55 - page 3, 1ine 47 10,26,27. US 3 661 786 A (DESFORGES MALCOM) 9 May 1972 1-9 see abstract see column 1, line 60 - column 2, line 30 see column 3, line 28 - column 4, line 6 see claims Patent family members are listed in annex. Further documents are listed in the continuation of box C. Special categories of cited documents: "T" later document published after the international filing date or priority date and not in conflict with the application but "A" document defining the general state of the art which is not cited to understand the principle or theory underlying the considered to be of particular relevance Invention "E" earlier document but published on or after the International "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to filing date involve an inventive step when the document is taken alone "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another "Y" document of particular relevance; the claimed invention citation or other special reason (as specified) cannot be considered to Involve an inventive step when the document is combined with one or more other such docu-"O" document referring to an oral disclosure, use, exhibition or ments, such combination being obvious to a person skilled other means In the art. "P" document published prior to the international filling date but "&" document member of the same patent family later than the priority date claimed Date of mailing of the international search report Date of the actual completion of the international search 14/12/1998 27 November 1998 Authorized officer Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Panzica, G Fax: (+31-70) 340-3016

INTERNATIONAL SEARCH REPORT

Inte onal Application No
PCT/EP 98/03327

	Citation of document, with indication where appropriate of the relevant passages	Relevant to claim No.
ategory * :	Citation of document, with indication, where appropriate, of the relevant passages	
	EP 0 758 018 A (GIST BROCADES BV) 12 February 1997 cited in the application see abstract see page 2, line 49 - page 4, line 4 see examples see claims	1-21, 23-25
	EP 0 304 332 A (NOVO INDUSTRI AS)	10-18,
	22 February 1989 see the whole document	26,27 1-9
	DE 33 44 104 A (HENKEL KGAA) 13 June 1985 see the whole document	10,26,27
		,
		•
	•	
,		
ĺ		

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inte onal Application No PCT/EP 98/03327

Patent document cited in search report			Publication date		atent family member(s)	Publication date	
EP	0257996	A	02-03-1988	FI	863393 A	23-02-1988	
		•		AT	123208 T	15-06-1995	
				CA	1335544 A	16-05-1995	
				DE	3751325 D	06-07-1995	
			•	DE	3751325 T	19-10-1995	
			•	DK	431787 A	23-02-1988	
				ES	2074979 T	01-10-1995	
				FI	870752 A,B,	24-08-1988	
				JP	63157938 A	30-06-1988	
				NO	175033 B	16-05-1994 	
US	3661786	Α	09-05-1972	NONE			
EP	0758018	A	12-02-1997	AU .	6073296 A	06-02-1997	
				CA	2182236 A	29-01-1997	
	•			CN	1159208 A	10-09-1997	
			,	CZ	9700874 A	18-03-1998	
	, A			WO	9705245 A	13-02-1997	
				JP	9154576 A	17-06-1997	
				PĻ	319347 A	04-08-1997	
				SK	40697 A	08-10-1997	
				US 	5827709 A	27-10-1998 	
EP	0304332	Α	22-02-1989	DE	3882301 A	19-08-1993	
				DE	3882301 T	21-10-1993	
	•			DK	436888 A,B,	22-02-1989	
				JP	1112983 A	01-05-1989	
				JP	2647695 B	27-08-1997	
				MX	12725 A	01-08-1993 	
DE	3344104	Α	13-06-1985	DK	579184 A	08-06-1985	
				EP	0168526 A	22-01-1986	